

LIFELINE INTERIOR

Stain and Sealer for Interior Log Walls and Millwork

Enhance the natural beauty and grain of your interior log walls and ceilings with Lifeline Interior finish. It provides a breathable yet tough film finish that is easily washed, cleaned and dusted. Lifeline reduces the absorption of normal household odors into the wood.

Lifeline Interior is non-flammable and virtually odorless. It will not yellow and lets the natural look and beauty of all types of wood show through for years to come. Lifeline Interior can be used on all new and existing log homes. Application methods and coverage rates are the same as Lifeline Exterior.



Lifeline Interior will be the only finish you'll ever need to apply inside your home. You may also use Lifeline Interior as a stain and sealer before the application of Acrylic Gloss or Satin.

Lifeline Interior Colors



Features and Statistics

- A breathable sealer
- Mold inhibitors

- **Non-yellowing and quick drying**
- **Semi-transparent**
- **Inhibits odor penetration**
- **Cleanable surface**
 - [MSDS](#) 
 - [LIFELINE Application Guide](#) 

To view and/or print MSDS sheets or labels you need Acrobat Reader. If you don't have Acrobat Reader installed on your computer, [click here](#) for a free download.

Shelf Life	<ul style="list-style-type: none"> • 1 year
Application Temperature	<ul style="list-style-type: none"> • 40° to 90°
Application Methods	<ul style="list-style-type: none"> • Airless Sprayer • Brush • Back-brushing required
Surface Preparation	<ul style="list-style-type: none"> • Clean and Dry • Free of mold and mildew • Never use steel wool
Frequency	<ul style="list-style-type: none"> • Long life
Special Instructions	<ul style="list-style-type: none"> • 2 coats. Must be back-brushed. • Stir every 15 minutes. • Maintain a wet edge to prevent lap marks. • 1-2 coats depending on desired color and finish
Drying Time	<ul style="list-style-type: none"> • Dry to the touch in 1 hour and cures in 3 days

Lifeline Interior

5 gal (50 lb) pail

1 gal (10 lb)



LIFELINE INTERIOR Coverage Rate per Gallon

First Coat	350-450 square feet
Second Coat	600-800 square feet