



Wood Brightener for Cedar & Redwood

892

| DESCRIPTION | CHARACTERISTICS | SPECIFICATIONS |
|---|---|--|
| <p>Wood Brightener for Cedar and Redwood is designed to clean, brighten and condition cedar, redwood and other substrates prior to applying TWP® Total Wood Preservative.</p> <p>Product Advantages:</p> <ul style="list-style-type: none"> ➤ Restores Grayed and Weathered Wood to its Natural Color ➤ Powerful Cleaner Designed to Clean, Brighten and Condition ➤ 100% Biodegradable- Will Not Harm Plants or Pets ➤ Removes Tannin and Nail Bleed ➤ Use Full Strength to Remove Iron, Rust, and Metal Stains on all Surfaces including Vinyl, Aluminum Siding and Concrete Driveways ➤ Removes Mill Glaze from New Woods ➤ May be Used to Clean Previously Painted or Stained Surfaces in Preparation for Recoating | <p>Weight/Gallon: 8.7</p> <p>Coverage: One gallon makes 5 gallons. Approximately 200 sq. ft. per gallon or 1000 sq. ft. per container.</p> <p>Where to Use: For use on exterior wood surfaces made of cedar and redwood that need to be cleaned and brightened.</p> <p>Surface Preparation: Do not apply product if surface and air temperatures are below 50°F. or above 90°F. Apply only to cool surfaces. Have the following ready before using product: a garden hose with nozzle, proper chemical resistant gloves, eye protection, 5 gallon plastic mixing container, a stiff bristle broom brush and protective plastic drop cloths. To prevent damage, pre-wet foliage and surrounding work area with water and cover with plastic drop cloths. Wear proper chemical resistant gloves, eye protection and apparel to protect your skin.</p> <p><i>*TWP® is a registered trademark of Amteco, Inc.</i></p> | <p>Material Preparation: Shake product thoroughly. In a clean 5 gallon plastic mixing container dilute 1 part Brightener with 4 parts tap water. Test small hidden area to see if desired results are achieved before applying. Lightly dampen surfaces prior to cleaning. Stir diluted solution thoroughly. For hard to clean, dark, weathered wood surfaces and for rust removal, use product full strength. Do not apply product if surface and air temperatures are below 50° F or above 90° F.</p> <p>Application: Apply solution liberally with a TWP® pump sprayer, brush, mop or roller. Keep surface wet for 10-15 minutes. Reapply solution as needed to keep surface wet and foaming during the cleaning period. Wet surfaces will be slippery. Scrub surface using stiff bristle broom brush. Solution will foam. After 10-15 minute cleaning period, rinse surface using garden hose with nozzle at maximum pressure or use pressure washer at 500 PSI. Surfaces other than wood may be dulled if not rinsed quickly. Repeat the above procedure on extremely dirty surfaces. All prepared surface to dry 48 hours minimum before applying TWP® Total Wood Preservative.</p> <p>Caution: If not used properly, a pressure washer may damage wood. KEEP OUT OF REACH OF CHILDREN! USE CAUTION WHEN USING WOOD BRIGHTENER FOR CEDAR & REDWOOD, WET SURFACES WILL BE SLIPPERY. Wash thoroughly after handling. Do not ingest. Wear proper chemical resistant gloves and eye protection.</p> <p>Clean Up: Rinse all equipment with water before storage or reuse. Dispose of in accordance with federal, state, and local regulations regarding pollution.</p> |

The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. **HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.

CAUTION: VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN! BEFORE using this product it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact the manufacturer.

Date: Oct-06