



PRODUCT DATA SHEET

Solid-Strip

893

DESCRIPTION	CHARACTERISTICS	SPECIFICATIONS
<p>Solid-Strip is designed for industrial strength stripping. It will remove heavy coated finishes and is ideal for most solid color stains, water-based and latex paints. Use Solid-Strip on decks, logs, or any wood surface that needs restoring. (For 100% acrylic water-based products, use a conventional paint stripper.)</p> <p>Product Advantages:</p> <ul style="list-style-type: none"> ➤ Prepares Wood Surface for Any Type Re-coating ➤ Removes Weathered Stains and Wood Sealers ➤ Removes Oil, Latex and Water-Based Finishes ➤ Tackles the Tough Stripping Jobs ➤ Easy Application and Removal 	<p>Coverage: 100-200 sq. ft. per gallon</p> <p>Dry Time: Product should sit for a minimum of 15 minutes, however, do not allow product to dry prior to rinsing.</p> <p>Shelf Life: One year if unopened and stored in a cool dry area. Always rotate stock.</p> <p>Conditions to Avoid: Avoid contact with aluminum, zinc or magnesium alloys. Avoid contact with skin.</p> <p>Surface Preparation: Pre-wet and cover the surrounding work area and vegetation to ensure no damage occurs.</p> <p><i>*TWP® is a registered trademark of Amteco, Inc.</i></p>	<p>Application: Apply Solid-Strip liberally to wood surfaces. Always test a small inconspicuous area to see if the desired result will be achieved. Best application results are with a TWP® garden sprayer, although a brush or roller can also be used. Product should sit for a minimum of 15 minutes, however do not allow product to dry. After sitting you may begin to scrub. When scrubbing applied area, use synthetic, stiff bristle brush (do not use a wire or natural bristle brush) Rinse thoroughly with hose or pressure washer. A pressure washer will show the best results, however, do not exceed 1000 PSI. If stubborn areas persist, re-apply Solid Strip and follow steps 2 and 3. Wood may darken after stripping. Use Gemini's Wood Brightener for Cedar and Redwood to revive color.</p> <p>Caution: This product contains Potassium Hydroxide, which can be dangerous. KEEP OUT OF REACH OF CHILDREN! FATAL IF SWALLOWED. Wash thoroughly after handling. Do not ingest. Wear safety glasses and gloves. If not used properly a pressure washer may damage wood. USE CAUTION WHEN WORKING WITH SOLID-STRIP, WET SURFACES WILL BE SLIPPERY.</p> <p>Clean Up: Dispose of in accordance with federal, state, and local regulations regarding pollution.</p>

The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. **HOWEVER, GEMINI MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** UNDER NO CIRCUMSTANCES SHALL GEMINI BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF GEMINI FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY GEMINI SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.

CAUTION: DANGER! FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN! BEFORE using this product it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact the manufacturer.

Date: Oct-06